

Ecoflex® 15

flexible, low loss and stray radiation resistant



Ecoflex 15 is a flexible low loss 50 ohm coaxial cable for the frequency range up to 6 GHz. Advanced manufacturing techniques combined with the use of a low loss PE-LLC dielectric with a foaming rate of more than 70% result in very low attenuation values.

The unique construction of Ecoflex 15 combines the excellent attenuation properties of non-flexible solid inner conductor 1/2" cables with the high flexibility of cables manufactured with stranded inner conductors. The high flexibility of Ecoflex 15 is further enhanced through the use of an oxygen-free copper inner conductor containing 7 stranded bare copper wires. During a special manufacturing process the inner conductor is continuously compressed, calibrated and then pre-coated to achieve good attenuation, good return loss values and stable impedance matching. Another advantage of Ecoflex 15 its double shielding: an overlapping copper foil and an additional shield braiding of bare copper wires with 75 % coverage ensure a high screening attenuation of > 90 dB at 1 GHz.

The black PVC jacket of Ecoflex 15 is UV-stabilized. For the easier installation of this cable, solderless N, UHF and 7-16 DIN connectors were developed. They can be assembled in a short time without special tools. Ecoflex 15 is the right choice, when an extremely flexible, low loss and microwave rated cable is required. It can be used for numerous

RF applications. Especially in cases with long distances and critical connections, where every „dB“ is important, Ecoflex 15 offers a lot of advantages.

Key features

Diameter	14,6 ± 0,3 mm
Impedance	50 ± 2 Ω
Attenuation at 1 GHz/100 m	9,80 dB
f max	6 GHz

Characteristics

- Jacket material according to DIN EN 50290-2-22 (VDE 0819), compound type TM 52 (HD 624.2)
- Flame retardant according to IEC 60332-1-2
- RoHS compliant (Directive 2011/65/EC)
- UV-resistant

Technical data

Inner conductor	Stranded bare copper wire
Inner conductor Ø	4,5 mm (7 x 1,5 mm)
Dielectric	foamed Polyethylene (PE) with skin
Dielectric Ø	11,3 mm
Outer conductor 1	copper foil overlapped
Shielding factor	100%
Outer conductor 2	shield braiding of bare copper wires
Shielding factor	75%
Outer conductor Ø	12,1 mm
Jacket	PVC black, UV-resistant
Weight	245 kg/km
Min. Bending radius	4XØ single, 8XØ repeated
Temperature range	-55 to +85°C Transport & fixed installation -40 to +85°C Flexible use
Pulling strength	1300 N

Electrical data at 20°C

Capacity (1 kHz)	78 nF/km
Velocity factor	0,85
Screening attenuation 1 GHz	≥ 90 dB
DC-resistance Inner conductor	≤ 1,5 Ω/km
DC-resistance Outer conductor	5,0 Ω/km
Insulation resistance	≥ 10 GΩ*km
Test voltage (Inner conductor/Outer conductor rms 50 Hz 1 Min.)	1000 V
Max. Voltage	5 kV

	Ecoflex 15	RG 213/U	RG 58/U
Capacity	78 pF/m	101 pF/m	102 pF/m
Velocity factor	0,85	0,66	0,66
Attenuation (dB/100m)			
10 MHz	0,86	2,00	5,00
100 MHz	2,81	7,00	17,00
500 MHz	6,70	17,00	39,00
1000 MHz	9,80	22,50	54,60
3000 MHz	18,30	58,50	118,00


Typ. Attenuation (db/100 m at 20°C)

5 MHz	0,60	1000 MHz	9,80
10 MHz	0,86	1296 MHz	11,40
50 MHz	1,96	1500 MHz	12,40
100 MHz	2,81	1800 MHz	13,80
144 MHz	3,40	2000 MHz	14,60
200 MHz	4,05	2400 MHz	16,20
300 MHz	5,00	3000 MHz	18,30
432 MHz	6,10	4000 MHz	21,60
500 MHz	6,70	5000 MHz	24,60
800 MHz	8,60	6000 MHz	27,50

Max. Power handling (W at 40°C)

10 MHz	6.327	2400 MHz	326
100 MHz	1.928	3000 MHz	284
500 MHz	810	4000 MHz	237
1000 MHz	547	5000 MHz	206
2000 MHz	364	6000 MHz	183

Typ. Attenuation (db/100 m at 20°C)



Typ. Return loss

